

---

# Multidimensional Sevilla Carpets Associated with P Systems

Miguel A. Gutiérrez-Naranjo, Mario J. Pérez-Jiménez,  
Agustín Riscos-Núñez

Research Group on Natural Computing  
Department of Computer Science and Artificial Intelligence  
University of Sevilla  
Avda. Reina Mercedes s/n, 41012 Sevilla, Spain  
E-mail: {magutier,marper,ariscosn}@us.es

**Summary.** In this paper we address the problem of describing the complexity of the evolution of a P system. This is especially difficult in the case of P systems where the number of membranes increases along the computation, via division or creation of membranes. In these cases the number of steps of a computation is not sufficient to evaluate the complexity. Sevilla Carpets were introduced in [1], and they describe the space-time complexity of P systems. Based on them, we define a four-dimensional manifold which can be used to compare evolutions of P systems.

## 1 Introduction

The evolution of a P system is a complex process where (eventually) a large number of symbol-objects, membranes and rules are involved. In the case of P systems where the number of membranes increases along the computation, via creation or division of membranes, the problem of describing the complexity of the computational process becomes especially difficult. In these cases, due to the parallelism intrinsic to P systems, an exponential number of membranes can be obtained in polynomial time. This feature makes these models of P systems a powerful tool to attack NP-complete problems and, indeed, several efficient solutions to these types of problems have been presented both in the model of P systems with *active membranes* (see, e.g., the Partition [2], Subset Sum [12], Knapsack [13], Bin Packing [14], SAT [15] or Validity [16]) and P systems with *membrane creation* (see, e.g., SAT [4], QSAT [5] or Subset Sum [6]).

These solutions are proposed in the framework of *Recognizer P systems with external output* [13]. The basic idea in these solutions is the construction of an exponential number of membranes (*workspace*) in polynomial time and the use of each membrane as an independent computational device. All membranes evolve *in parallel* and the computation has a polynomial cost in time. The process ends with

a final stage (with a polynomial cost) that checks the answers of these devices and sends an answer to the environment.

The cost in *time* (number of cellular steps) of these solutions is polynomial, but it is clear that the time is not the unique variable that we need to consider in order to evaluate the “complexity” of the process. G. Ciobanu, Gh. Păun and Gh. Ştefănescu presented in [1] a new way to describe the complexity of a computation in a P system. The so-called *Sevilla Carpet* is an extension of the notion of Szilard language from grammars to the case when several rules are used at the same time.

In [3], new parameters for the study of the descriptive complexity of P systems were introduced and several examples of a graphical representation of Sevilla carpets and of the usefulness of these parameters for comparing different solutions for a given problem were provided.

In this paper we extend the definition of Sevilla Carpets to describe the computations of P systems. We present a four dimensional manifold which can be used for a better understanding of the complexity of a P system. The graphical representation of this four-dimensional manifold is carried out via projections on three-dimensional spaces.

The paper is organized as follows. In Section 2 we first give some preliminary notions on *recognizer P systems*. Section 3 presents the Sevilla Carpets together with some parameters related with them, and also a graphical example is shown. Section 4 introduces the idea of considering an additional dimension in the carpet, leading to four-dimensional Sevilla carpets. Finally, some comments are provided.

## References

1. G. Ciobanu, Gh. Păun, Gh. Ştefănescu: Sevilla carpets associated with P systems. In *Proceedings of the First Brainstorming Week on Membrane Computing* (M. Cavaliere, C. Martín-Vide, Gh. Păun eds.), Report GRLMC 26/03, Rovira i Virgili University, 2003, 135–140.
2. M.A. Gutiérrez-Naranjo, M.J. Pérez-Jiménez, A. Riscos-Núñez: A fast P system for finding a balanced 2-partition. *Soft Computing*, 9, 5 (2005).
3. M.A. Gutiérrez-Naranjo, M.J. Pérez-Jiménez, A. Riscos-Núñez: On descriptive complexity of P systems. In *Membrane Computing, 5th International Workshop, WMC5* (G. Mauri, Gh. Păun, M.J. Pérez Jiménez, G. Rozenberg, A. Salomaa, eds.), LNCS 3365 (2005), 320–330.
4. M.A. Gutiérrez-Naranjo, M.J. Pérez-Jiménez, F.J. Romero-Campero: Solving SAT with membrane creation. Accepted paper for *New Computational Paradigms CiE 2005*, Amsterdam, June 8-12, 2005.
5. M.A. Gutiérrez-Naranjo, M.J. Pérez-Jiménez, F.J. Romero-Campero: A linear solution for QSAT with membrane creation. Submitted, 2005.
6. M.A. Gutiérrez-Naranjo, M.J. Pérez-Jiménez, F.J. Romero-Campero: A linear solution of Subset Sum problem by using membrane creation. Accepted paper in the *First International Work-Conference on the Interplay between Natural and Artificial Computation*, IWINAC-2005, Las Palmas de Gran Canaria, June 15-18, 2005.

7. M.A. Gutiérrez-Naranjo, M.J. Pérez-Jiménez, A. Riscos-Núñez: A simulator for confluent P systems. In *Proceedings of the Third Brainstorming Week on Membrane Computing* (M.A. Gutiérrez, A. Riscos, F.J. Romero, D. Sburlan, eds.), Report RGNC 01/05, University of Seville, 2005, in press.
8. E. Mäkinen: A bibliography on Szilard languages. Dept. of Computer and Information Sciences, University of Tampere, <http://www.cs.uta.fi/reports/pdf/Szilard.pdf>
9. A. Mateescu, A. Salomaa: Aspects of classical language theory. In *Handbook of Formal Languages, vol. 1* (G. Rozenberg, A. Salomaa, eds.), Springer-Verlag, Berlin, 1997.
10. Gh. Păun: *Membrane Computing. An Introduction*. Springer-Verlag, Berlin, 2002.
11. Gh. Păun, M.J. Pérez-Jiménez: Recent computing models inspired from biology: DNA and membrane computing. *Theoria*, 18, 46 (2003), 72–84.
12. M.J. Pérez-Jiménez, A. Riscos-Núñez: Solving the Subset Sum problem by active membranes. *New Generation Computing*, in press.
13. M.J. Pérez-Jiménez, A. Riscos-Núñez: A linear solution for the Knapsack problem using active membranes. In *Membrane Computing, International Workshop, WMC 2003, Tarragona, Spain, July 2003, Revised Papers* (C. Martín-Vide, Gh. Păun, G. Rozenberg, A. Salomaa, eds.), LNCS 2933 (2004), 250–268.
14. M.J. Pérez-Jiménez, F.J. Romero-Campero: Solving the BIN PACKING problem by recognizer P systems with active membranes. In *Proceedings of the Second Brainstorming Week on Membrane Computing* (Gh. Păun, A. Riscos, A. Romero, F. Sancho, eds.), Report RGNC 01/04, University of Seville, 2004, 414–430.
15. M.J. Pérez-Jiménez, A. Romero-Jiménez, F. Sancho-Caparrini: A polynomial complexity class in P systems using membrane division. In *Proceedings of the Fifth International Workshop on Descriptive Complexity of Formal Systems* (E. Csuhaj-Varjú, C. Kintala, D. Wotschke and Gy. Vaszyl, eds.), 2003, 284–294.
16. M.J. Pérez-Jiménez, A. Romero-Jiménez, F. Sancho-Caparrini: Solving VALIDITY problem by active membranes with input. In *Proceedings of the First Brainstorming Week on Membrane Computing* (M. Cavaliere, C. Martín-Vide, Gh. Păun eds.), Report GRLMC 26/03, Rovira i Virgili University, 2003, 279–290.
17. A. Salomaa: *Formal Languages*. Academic Press, New York, 1973.
18. P systems web page <http://psystems.disco.unimib.it/>

